## NSN 5935-01-072-3909

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-072-3909



**Body Style:** Straight type **Overall Length:** 4.350 inches **Overall Height:** 0.565 inches **Overall Width:** 0.250 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 4.100 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping

**Guide Design And Location:** 

D shape pin left-hand at 12 oclock and d shape socket right-hand at 12 oclock

**Insert Material Specification:** 

Mil-m-14 military specification single material response single mating end or mil-p-19833 military specification single material response single mating end

**Included Contact Quantity:** 

70 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

## NSN 5935-01-072-3909

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.