

View Online at <https://aerobasegroup.com/nsn/5935-01-072-5303>

Body Style:

Straight shape

Overall Length:

1.340 inches

Overall Height:

0.505 inches

Overall Width:

0.270 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.094 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

333.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Screw lock pin

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-w-401 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.