## NSN 5935-01-072-8526



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-072-8526 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/card guide **Overall Length:** 1.760 inches **Overall Height:** 0.835 inches **Overall Width:** 0.290 inches **Distance Between Mounting Facility Centers:** 1.600 inches **Board Accommodated Length:** 1.180 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** 0.120 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** 

Thready Qty Per Inch (tpi):

56

**Thread Size:** 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# NSN 5935-01-072-8526

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Glass single mating end and plastic polyester single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

## **Included Contact Quantity:**

20 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.020 gold grains, troy

#### **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

#### **Unit Of Measure:**

## Demilitarization:

No

# Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.