Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-072-8530

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.440 inches
Overall Diameter:
0.690 inches
Environmental Protection:
Shock resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
0.675 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
120.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Compression nut
Thready Qty Per Inch (tpi):
28
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material:	
	roethylene single mating end
	reatment Specification:
	2, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating	end single contact grouping
Contact Material S	pecification:
Qq-c-533 comp 172	federal specification single material response single mating end single contact grouping
Shell Material:	
Copper alloy 360	
Shell Material Spe	cification:
Qq-b-626, 1/2 hard	federal specification single material response
Insert Material Spe	cification:
Mil-p-19468 military	specification single material response single mating end
Included Contact (Quantity:
1 single mating end	single contact grouping
Bushing Accommo	odation Hole Shape:
Round w/flat	
Included Contact 7	Гуре:
Triaxial pin single m	ating end single contact grouping
Precious Material	And Location:
Contact surface gol	d
Precious Material	And Weight:
0.005 gold grains, t	roy
Precious Material:	
Gold	
Thread Series Des	ignator:
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military St	andard):
Mil-g-45204 spec.	