Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-072-8689

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Threaded Device Type:
Mating End Quantity:
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
63.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
40 Thread Since
Thread Size:
0.112 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Metal ferrous single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings

NSN 5935-01-072-8689

Electrical Receptacle Connector - Page 2 of 2



Insert Materi	
Glass single r	
	ace Treatment Specification:
-	nilitary specification single treatment response single mating end all contact groupings
Terminal Typ	be:
Solder well si	ngle mating end all contact groupings
Shell Materia	d:
Metal ferrous	
Shell Surface	e Treatment:
Tin and nicke	I
Included Cor	ntact Quantity:
37 single mat	ing end 2nd contact grouping
Included Cor	ntact Type:
Round pin sir	gle mating end all contact groupings
Precious Ma	terial And Location:
Contact surfa	ces gold
Precious Ma	terial And Weight:
0.039 gold gra	ains, troy
Precious Ma	terial:
Gold	
Thread Serie	s Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 s	pec.