## NSN 5935-01-073-4643

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-073-4643

view Offilitie at https://defobasegroup.com/nsi//0900-01-070-4040
Body Style:
Straight shape, external coupling
Overall Length:
1.552 inches
Overall Height:
1.234 inches
Overall Width:
1.234 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
Between 0.400 inches and 0.462 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-23 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
22.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
158.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Terminal Location:
Back single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Included Contact Quantity:

Included Contact Type:

Round socket single mating end all contact groupings

22 single mating end 2nd contact grouping

## NSN 5935-01-073-4643

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-c-26482 spec.