Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-073-8880

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Round flange mount, external coupling
Overall Length:
0.434 inches
Mounting Hole Circle Radius: 0.165 inches
Overall Diameter:
0.500 inches
Environmental Protection:
Environmental Protection: Moisture resistant and salt water resistant and vibration resistant
Distance From Mounting Shoulder To Rear Face:
0.059 inches
Threaded Device Type:
Coupling facility and mounting hole
Mating End Quantity:
1 Contact Position Arrangement Style:
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type: Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
36 and 56
Thread Size:
0.250 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Copper anoy single mating end single contact grouping
Gold single mating end single contact grouping
Contact Surface Treatment Specification:

Mil-g-45204, tx 1, grade c, cl 2 military specification single treatment response single mating end single contact grouping



## **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530, 1/2 hard federal specification single material response single mating end single contact grouping Shell Material: Copper alloy **Shell Surface Treatment:** Gold **Shell Surface Treatment Specification:** Mil-g-45204, type 1, grade c, cl 1 military specification single treatment response **Shell Material Specification:** Qq-c-530, 1/2 hard federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and body surface gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns and unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.