

View Online at <https://aerobasegroup.com/nsn/5935-01-074-8408>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

1.872 inches

Overall Diameter:

1.354 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Cable Entrance Diameter:

0.625 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

18-30 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

8

Thread Size:

1.125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

29 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0