

View Online at <https://aerobasegroup.com/nsn/5935-01-074-8639>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.790 inches

**Overall Diameter:**

0.250 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant

**Distance From Mounting Shoulder To Front Face:**

0.560 inches

**Mounting Facility Thickness:**

0.125 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 2nd mating end

**Contact Removability:**

Removable all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thready Qty Per Inch (tpi):**

36 and 36

**Thread Size:**

0.250 inches and 0.250 inches

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204b, type 1, class 2, grade c military specification single treatment response all mating ends all contact groupings

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends all contact groupings

**Shell Material:**

Steel

**Shell Material Specification:**

Qq-c-763, type 303 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Type:**

Round socket all mating ends all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204b spec.