

View Online at <https://aerobasegroup.com/nsn/5935-01-074-8671>

Body Style:

Straight shape

Overall Length:

Between 2.073 inches and 2.103 inches

Overall Height:

0.611 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and moisture proof and shock resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.086 inches and 0.091 inches

Distance Between Mounting Facility Centers:

Between 1.847 inches and 1.857 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 type 1, grade c military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification single treatment response

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.044 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.