

View Online at https://aerobasegroup.com/nsn/5935-01-074-8697

	hread Class:
2	a
т	hread Direction:
R	ight-hand
в	ody Style:
S	traight shape, external coupling
0	verall Length:
В	etween 1.023 inches and 1.165 inches
0	verall Height:
1	.188 inches
0	verall Width:
1	.188 inches
E	nvironmental Protection:
N	loisture proof and salt water resistant and vibration proof and waterproof
U	nthreaded Mounting Hole Diameter:
В	etween 0.148 inches and 0.154 inches
С	enter To Center Distance Between Mounting Facilities Parallel To Height:
0	.906 inches
D	istance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0	.906 inches
D	istance From Mounting Shoulder To Front Face:
B	etween 0.562 inches and 0.578 inches
Г	hreaded Device Type:
С	oupling facility
M	lating End Quantity:
1	
С	ontact Position Arrangement Style:
1	4s-5 single mating end
P	olarization Method:
K	ey, multiple key groove
Ir	nsert Position In Deg:
0	.0
S	hell Type:
S	olid
С	onnector Locking Method:
E	xternally threaded shell
Т	hready Qty Per Inch (tpi):
1	0
Т	hread Size:
0	.875 inches
Ir	nsert Material:
D	ubber single mating end



Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0