NSN 5935-01-074-9032



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-074-9032 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.094 inches **Overall Height:** 1.125 inches **Overall Width:** 1.125 inches **Environmental Protection:** Humidity resistant and corrosion resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.844 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.844 inches **Distance From Mounting Shoulder To Front Face:** 0.420 inches **Mating End Quantity: Contact Position Arrangement Style:** 4-nov single mating end **Contact Removability:** Removable single mating end single contact grouping **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Insert Material:

Rubber single mating end

Gold single mating end single contact grouping

NSN 5935-01-074-9032

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0