## NSN 5935-01-074-9170

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-074-9170 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.984 inches **Overall Height:** 3.937 inches **Overall Width:** 3.375 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 3.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.875 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 90 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Polarization Method:** 2 polarization posts Shell Type: **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.312 inches **Terminal Location:** 

**Contact Material:** 

Copper alloy all mating ends single contact grouping

Back all mating ends single contact grouping

## NSN 5935-01-074-9170

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold all mating ends single contact grouping or silver all mating ends single contact grouping
Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

**Terminal Type:** 

Solder well all mating ends single contact grouping

**Guide Design And Location:** 

D shape pin right-hand at 3 oclock

Shell Material:

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Included Contact Type:** 

Round socket all mating ends single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.180 gold grains, troy and 0.180 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Uns

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0