Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-075-3891

# Body Style:

Straight shape threaded

#### **Overall Length:**

1.780 inches

### **Overall Diameter:**

0.721 inches

### **Environmental Protection:**

Salt water resistant and shock resistant and vibration resistant

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

3 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

# Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

### **Polarization Method:**

Contact

### **Connector Locking Method:**

Spring friction

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### Contact Surface Treatment:

Tin single mating end single contact grouping

#### **Insert Material:**

Rubber single mating end

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Included Contact Quantity:

3 single mating end single contact grouping

# **Bushing Accommodation Hole Shape:**

Round

# Included Contact Type:

Round pin single mating end single contact grouping

# Shelf Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0