Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-075-7187

## **Body Style:**

Straight shape, external coupling

**Overall Length:** 

2.422 inches

## **Overall Height:**

0.828 inches

## **Overall Width:**

0.828 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.594 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.594 inches

### Distance From Mounting Shoulder To Front Face:

Between 0.400 inches and 0.862 inches

#### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

40394 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

Shell Type:

Solid

## **Connector Locking Method:**

Bayonet latch

**Terminal Location:** 

Back single mating end single contact grouping

# Terminal Type:

Crimp single mating end single contact grouping

# Included Contact Quantity:

4 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-26482 spec.