NSN 5935-01-076-1846

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-076-1846 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 1.350 inches **Overall Height:** 1.235 inches **Overall Width:** 0.250 inches **Distance Between Mounting Facility Centers:** 1.150 inches **Threaded Device Type:** Mounting bushing and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Fk-I20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping Shell Type: Split Radio Frequency Type Contact Characteristic Impedance In Ohms: 0.020 single mating end single contact grouping **End Application:** Xm1 tank Thread Length: 0.130 inches **Unable To Decode:** Unable to decode and unable to decode Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-01-076-1846

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
18 single mating end single contact grouping
Special Features:
Jackscrew type-male and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold
Supplementary Features:
Mounting method - jackscrew and jacksocket
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No