NSN 5935-01-076-4510

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-076-4510 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.922 inches **Overall Diameter:** 1.438 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 0.660 inches **Mounting Facility Thickness:** 0.094 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 27 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.187 inches **Terminal Location:** Back single mating end single contact grouping

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment:

NSN 5935-01-076-4510

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Wire loop single mating end single contact grouping
Shell Surface Treatment:
Tin and cadmium
Included Contact Quantity:
27 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.027 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0