## NSN 5935-01-076-6417

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-076-6417 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.531 inches **Overall Diameter:** 1.625 inches **Distance From Mounting Shoulder To Front Face:** 1.156 inches **Mounting Facility Thickness:** 0.235 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** C single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Terminal Type:** 

Solder well single mating end single contact grouping

**Included Contact Quantity:** 

1 single mating end single contact grouping

## NSN 5935-01-076-6417

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:	
Round	
Included Contact Type:	
Coaxial socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.001 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A039b0	