Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-076-8523

Body Style:
Straight type
Overall Length:
3.280 inches
Overall Height:
0.650 inches
Overall Width:
0.600 inches
Unthreaded Mounting Hole Diameter:
0.152 inches
Distance Between Mounting Facility Centers:
2.946 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Bracket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.