

View Online at <https://aerobasegroup.com/nsn/5935-01-077-5367>

**Body Style:**

Straight type

**Overall Length:**

3.688 inches

**Overall Height:**

Between 0.720 inches and 0.760 inches

**Overall Width:**

0.430 inches

**Environmental Protection:**

Moisture resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.093 inches and 0.095 inches

**Distance Between Mounting Facility Centers:**

3.210 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Contact

**Connector Locking Method:**

Spring friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533, alloy 25 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty mfh military specification single material response single mating end

**Included Contact Quantity:**

98 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.098 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.