Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-077-5883

Body Style:

Straight shape, external coupling

Overall Length:

1.190 inches

Bushing Diameter:

0.560 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Environmental Protection:

Shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.530 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.530 inches

Distance From Mounting Shoulder To Front Face:

0.760 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping



Contact Surface Treatment Specification: Qq-s-365 federal specification single treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** Qq-b-626, alloy 360, 1/2 hard federal specification single material response single mating end single contact grouping Shell Material: Copper alloy **Shell Material Specification:** Qq-b-626, alloy 360 1/2 hard federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material And Weight:** 0.005 silver grains, troy **Precious Material:** Silver Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0