Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-077-7166

Thread	Class:

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape

## **Overall Length:**

1.500 inches

#### **Overall Height:**

0.531 inches

#### **Overall Width:**

0.343 inches

### **Distance Between Mounting Facility Centers:**

1.250 inches

#### **Threaded Device Type:**

Mounting stud

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

26 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### Polarization Method:

Guide pin/socket

### Thready Qty Per Inch (tpi):

56

## Thread Size:

0.086 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Terminal Type:**

Solder well single mating end single contact grouping

# Insert Material Specification:

Mil-p-19833 ty gdi-30 military specification single material response single mating end

## Unable To Decode:

Unable to decode and unable to decode

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 20 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Removed contacts a-b-c (upper case) and contacts a-c-d (lower case) **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.