NSN 5935-01-077-8688

Body Style:

Overall Length:

Straight shape, external coupling

Shell Surface Treatment:

Passivate

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-077-8688

0.703 inches
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
Between 0.317 inches and 0.322 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Stainless steel

NSN 5935-01-077-8688

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 79 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.079 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-dtl-38999 spec.