## NSN 5935-01-077-9774

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-077-9774

| View Online at https://aerobasegroup.com/nsn/5935-01-077-9774                              |
|--|
| Body Style:  |
| Straight shape w/clamp   |
| Overall Length:  |
| 0.870 inches   |
| Overall Width:   |
| 0.380 inches   |
| Environmental Protection:  |
| Shock resistant and vibration resistant  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| "18, 18-20" single mating end  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping                                     |
| Polarization Method:   |
| Guide pin/socket   |
| Connector Cable Strain Relief Method:  |
| Cable clamp  |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping                                     |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Insert Material:   |
| Plastic diallyl phthalate single mating end  |
| Terminal Type:   |
| Solder well single mating end single contact grouping                                      |
| Insert Material Specification:   |
| Mil-p-19833, type gdi-30 military specification single material response single mating end |
| Included Contact Quantity:   |
| 18 single mating end single contact grouping   |
| Included Contact Type:   |
| Round socket single mating end single contact grouping                                     |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.018 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Shelf Life:  |

N/a

## NSN 5935-01-077-9774

Electrical Plug Connector - Page 2 of 2



| Ini | 1 ( | Of | ΝЛ | മാ | e i | ırc | ٠. |
|-----|-----|----|----|----|-----|-----|----|
|     |     |    |    |    |     |     |    |

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.