

View Online at <https://aerobasegroup.com/nsn/5935-01-077-9778>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.175 inches

Overall Diameter:

1.766 inches

Environmental Protection:

Moisture proof and vibration proof

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

23-1 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

345.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thread Length:

0.188 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.312 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Resin synthetic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.100 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-27599 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms20028 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.