

View Online at <https://aerobasegroup.com/nsn/5935-01-078-0297>

**Body Style:**

Straight shape

**Overall Length:**

1.541 inches

**Overall Height:**

0.663 inches

**Overall Width:**

0.494 inches

**Unthreaded Mounting Hole Diameter:**

0.086 inches

**Distance Between Mounting Facility Centers:**

1.312 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

7 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 ty ii, cl 1 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 cl 4 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416 ty ii, cl 2 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 ty sdg military specification single material response single mating end

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.