NSN 5935-01-078-0299

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-078-0299 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.531 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock proof and weatherproof **Unthreaded Mounting Hole Diameter:** 0.056 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method:** Internally threaded shell Thready Qty Per Inch (tpi): 36 Thread Size: 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic fluorocarbon single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:**

Copper alloy

NSN 5935-01-078-0299

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0