NSN 5935-01-078-1591

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-078-1591 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Square flange mount **Overall Length:** 0.500 inches **Overall Height:** 0.625 inches **Overall Width:** 0.223 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant and shock proof **Unthreaded Mounting Hole Diameter:** 0.102 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.481 inches **Distance From Mounting Shoulder To Rear Face:** 0.125 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Osm single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Frequency Rating:** 18000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Shrinkable tubing Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-078-1591

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530, half hard federal specification single material response single mating end single contact grouping
Shell Material:
Steel comp 303
Shell Material Specification:
Qq-s-764, cond a federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.