## NSN 5935-01-078-3439

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-078-3439

**Body Style:** Straight shape **Overall Length:** Between 3.940 inches and 3.963 inches **Overall Height:** Between 0.725 inches and 0.775 inches Overall Width: 0.250 inches **Environmental Protection:** Vibration resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.094 inches **Distance Between Mounting Facility Centers: 3.700** inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

## NSN 5935-01-078-3439

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

64 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.064 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.