## NSN 5935-01-078-3995

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-078-3995

**Body Style:** Rectangular shape **Overall Length:** 3.840 inches **Overall Height:** 0.238 inches **Body Width:** 0.320 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration resistant **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end and glass single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping **Terminal Type:** 

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

#### **Included Contact Quantity:**

76 single mating end single contact grouping

#### **Included Contact Type:**

Flat socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# NSN 5935-01-078-3995

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.076 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.