Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-079-2518

## **Overall Height:**

1.812 inches

## **Overall Width:**

1.812 inches

## **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant

and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

## Mating End Quantity:

1

## **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

# **Insert Position In Deg:**

74.0

#### Shell Type:

Solid

### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

## **Features Provided:**

Pre-tinned terminal

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

### Shell Surface Treatment:

Nickel

#### **Included Contact Quantity:**

128 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

## Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No



**Fiig:** A039b0

Mil-std (military Standard):

Mil-c-38999 spec.