

View Online at <https://aerobasegroup.com/nsn/5935-01-079-7335>

Body Style:

Straight shape, internal coupling w/backshell

Overall Length:

1.690 inches

Overall Diameter:

1.375 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mating End Quantity:

1

Contact Position Arrangement Style:

18-24 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

45.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

24 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.024 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.