NSN 5935-01-079-7352

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-079-7352

Body Style:
Straight shape
Overall Length:
4.050 inches
Overall Height:
0.413 inches
Overall Width:
0.300 inches
Body Length:
3.260 inches
Unthreaded Mounting Hole Diameter:
0.100 inches
Distance Between Mounting Facility Centers:
3.100 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Latch
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic polyester single mating end
Contact Surface Treatment Specification:
$Mil-g-45204,\ type\ 2,\ cl\ 0\ military\ specification\ 1st\ treatment\ response\ single\ mating\ end\ single\ contact\ grouping\ and\ qq-n-290\ federal$
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping

Qq-p-330, comp a federal specification single material response single mating end single contact grouping

Included Contact Quantity:

Contact Material Specification:

50 single mating end single contact grouping

NSN 5935-01-079-7352

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Mtg holes are located on the front of item **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.