

View Online at <https://aerobasegroup.com/nsn/5935-01-079-7380>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.465 inches

**Overall Height:**

1.578 inches

**Overall Width:**

1.578 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.556 inches and 0.587 inches

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

22-41 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

225.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thread Length:**

0.290 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.312 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, grade e federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074, cl 3, grade b military specification single treatment response

**Shell Material Specification:**

Qq-a-367, 6061-t6 federal specification single material response

**Included Contact Quantity:**

27 single mating end 2nd contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.041 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3470 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Mil-std (military Standard):**

Mil-g-45204 spec.