Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-079-8589

Body Style:

Right angle type

Overall Length:

Between 8.770 inches and 8.830 inches

Overall Width:

Between 0.322 inches and 0.338 inches

Body Height:

Between 0.550 inches and 0.610 inches

Environmental Protection:

Corrosion resistant and shock resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.070 inches and 0.076 inches

Distance Between Mounting Facility Centers:

Between 8.590 inches and 8.610 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification

2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping



Guide Design And Location:
D shape pin right-hand at 6 oclock
Shell Material:
Aluminum alloy 6063
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, class 1a military specification single treatment response
Shell Material Specification:
Qq-a-200/9, t6 federal specification single material response
Insert Material Specification:
Mil-m-20693 military specification single material response single mating end
Included Contact Quantity:
130 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Special Features:
Item has two mounting holes on each end
Color:
Black
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.130 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.