NSN 5935-01-079-9305

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-079-9305 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.180 inches **Overall Height:** Between 1.850 inches and 1.870 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.495 inches and 2.505 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 158 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss **Connector Locking Method:** Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:**

Insert Material:

Plastic diallyl phthalate single mating end

Gold single mating end single contact grouping

NSN 5935-01-079-9305

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
158 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.