NSN 5935-01-080-1814

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-1814

| 5. c. april 200 100 100 100 100 100 100 100 100 100 |
|---|
| Body Style: |
| Rectangular shape center screwlock |
| Overall Length: |
| 1.734 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.484 inches |
| Overall Height: |
| 1.581 inches |
| Overall Width: |
| 0.450 inches |
| Environmental Protection: |
| Thermal shock resistant and vibration resistant and moisture resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 100.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic phenolic single mating end |
| Terminal Type: |
| Wire wrap single mating end single contact grouping |
| Included Contact Quantity: |
| 24 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.024 gold grains, troy |
| Precious Material: |
| Gold |
| Shalf Life: |

N/a

NSN 5935-01-080-1814

Electrical Receptacle Connector - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A039b0