Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-3320

# **Body Style:**

Rectangular shape

## **Overall Length:**

2.718 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

2.282 inches

## **Overall Height:**

0.615 inches

### **Overall Width:**

0.875 inches

### **Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

# **Unthreaded Mounting Hole Diameter:**

### 0.118 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

### 0.468 inches

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

50 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### Insert Material:

Plastic diallyl phthalate single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204 type 1, grade c military specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14 ty sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

50 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold



## **Precious Material And Weight:**

0.050 gold grains, troy

### **Precious Material:**

Gold

### Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-28748/6 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.