NSN 5935-01-080-6320

Included Contact Type:

Round socket single mating end 2nd contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-6320

Body Style:
Straight shape
Overall Length:
2.635 inches
Overall Width:
0.605 inches
Unthreaded Mounting Hole Diameter:
Between 0.086 inches and 0.091 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
5.0 single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and nickel single mating end all contact groupings
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-14, type gdi-30f military specification 1st material response single mating end and mil-m-14, type sdg-f military specification 2nd
material response single mating end
Included Contact Quantity:
39 single mating end 2nd contact grouping

NSN 5935-01-080-6320

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location
Contact surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.