

View Online at <https://aerobasegroup.com/nsn/5935-01-080-7231>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.125 inches

**Environmental Protection:**

Moisture resistant and shock resistant and vibration proof and salt water resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Maximum Frequency Rating:**

10000.0 megahertz single mating end single contact grouping

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-c-14550, class 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, class 1, grade c military specification 2nd treatment response single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 or qq-c-533, cond ht federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-14550 spec.