Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-080-7231

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

1.125 inches

# **Environmental Protection:**

Moisture resistant and shock resistant and vibration proof and salt water resistant

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Bnc single mating end

## **Contact Maximum Frequency Rating:**

10000.0 megahertz single mating end single contact grouping

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-c-14550, class 4 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 2, class 1,

grade c military specification 2nd treatment response single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 or qq-c-533, cond ht federal specification single material response single mating end single contact grouping

## Included Contact Quantity:

1 single mating end single contact grouping

#### Included Contact Type:

Coaxial socket single mating end single contact grouping

Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

#### Fiig:

A039b0

## Mil-std (military Standard):

Mil-c-14550 spec.