Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-7237

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.835 inches

Overall Height:

1.210 inches

Overall Width:

0.370 inches

Distance Between Mounting Facility Centers:

4.575 inches

Board Accommodated Length:

4.100 inches single board

Threaded Device Type:

Mounting hole

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Spring friction

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping



end

Insert Material:	
	thalate single mating end
Terminal Type:	
-	g end single contact grouping
Insert Material	
	gdi-30 military specification single material response single mating
Included Conta	-
	g end single contact grouping
Included Conta	
	le mating end single contact grouping
Precious Mater	ial And Location:
Contact surfaces	s gold
Precious Mater	ial And Weight:
0.080 gold grain	is, troy
Precious Mater	ial:
Gold	
Thread Series I	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measur	e:
Demilitarization	1:
No	
Fiig:	
A039b0	
Mil-std (military	/ Standard):
Mil-p-19833 spe	c.