NSN 5935-01-080-8127

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-8127 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.405 inches **Overall Diameter:** Between 1.610 inches and 1.641 inches **Distance From Mounting Shoulder To Front Face:** Between 0.691 inches and 0.707 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.187 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches Thready Qty Per Inch (tpi): 20 and 18 **Thread Size:** 1.000 inches and 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-01-080-8127

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|---|
| Aluminum alloy 6061 |
| Shell Surface Treatment: |
| Anodize |
| Shell Surface Treatment Specification: |
| Mil-a-8625 military specification single treatment response |
| Shell Material Specification: |
| Qq-a-367, t6 federal specification single material response |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round w/flat |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |