NSN 5935-01-080-9910

Crimp single mating end single contact grouping

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-080-9910

Straight shape, external coupling
Overall Length:
1.289 inches
Overall Height:
1.312 inches
Overall Width:
1.312 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.128 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.062 inches
Distance From Mounting Shoulder To Front Face:
0.820 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
17-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

NSN 5935-01-080-9910

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27656 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.