## NSN 5935-01-081-0187



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-081-0187 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.490 inches **Overall Diameter:** 2.068 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Distance From Mounting Shoulder To Front Face:** Between 0.761 inches and 0.781 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Back shell and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 26 number 20 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.290 inches Thready Qty Per Inch (tpi):

18 and 18

**Thread Size:** 

1.312 inches and 1.500 inches

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

## NSN 5935-01-081-0187

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Quantity:
6 single mating end 1st contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.