Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-081-0230

Thread Class: 2b Shead Direction: Right-hand Seal Material: Rubber, neoprene latex Overall Length: 1.781 inches Overall Width: 1.688 inches Cable Opening Diameter: Between 0.562 inches and 0.938 inches Cable Opening Quantity: 1 Preformed packing Size Designation: 24 Munting Facility Type And Quantity: 1 1 1 1 1 24 Munting Facility Type And Quantity: 1 1.500 inches 1.500 inches Auralionality 24 Munting Facility Type And Quantity: 1 1.600 inches 1.500 inches Material: 1.500 inches Munting alby Sufface Treatment: Cadmium and chromate
Thread Direction:Right-handSeal Material:Rubber, neoprene latexOverall Length:1.781 inchesOverall Width:1.688 inchesCable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:1Seal Type:Preformed packingSuber Spatiantion:24Mounting Facility Type And Quantity:11Threaded couplingThreaded coupling28Fired Size:1.500 inchesMaterial:Auminum alloySufface Treatment:
Right-hand Seal Material: Rubber, neoprene latex Overall Length: 1.781 inches Overall Width: 1.688 inches Cable Opening Diameter: Between 0.562 inches and 0.938 inches Cable Opening Quantity: 1 1 Seal Type: Preformed packing Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 1.500 inches Mearial: Auminum alloy Surface Treatment:
Seal Material: Rubber, neoprene latex Overall Length: 1.781 inches Overall Width: 1.688 inches Cobe Opening Diameter: Between 0.562 inches and 0.938 inches Coble Opening Quantity: 1 f Seal Type: Preformed packing Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling Thready Cup Per Inch (tpi): 28 Thread Size: 1.500 inches MateriaI: Aluminum alloy Surface Treatment:
Rubber, neoprene latex Overall Length: 1.781 inches Overall Width: 1.688 inches Cable Opening Diameter: Between 0.562 inches and 0.938 inches Cable Opening Quantity: 1 Seal Type: Preformed packing Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Overall Length:1.781 inchesOverall Width:1.688 inchesCable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:11Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Quy Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Auminum alloySurface Treatment:
1.781 inchesOverall Width:1.688 inchesCable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:1Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Auminur alloySurface Treatment:
Overall Width:1.688 inchesCable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:Cable Opening Quantity:1Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Cty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Atuminum alloySurface Treatment:
1.688 inchesCable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:Cable Opening Quantity:1Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Atuminum alloySurface Treatment:
Cable Opening Diameter:Between 0.562 inches and 0.938 inchesCable Opening Quantity:11Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Aluminum alloySurface Treatment:
Between 0.562 inches and 0.938 inchesCable Opening Quantity:11Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Firead Size:1.500 inchesMaterial:Aluminum alloySurface Treatment:
Cable Opening Quantity:1Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Finead Size:1.500 inchesMaterial:Aluminum alloySurface Treatment:
1 Seal Type: Preformed packing Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Seal Type:Preformed packingSize Designation:24Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Aluminum alloySurface Treatment:
Preformed packing Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling 1 threaded coupling Chready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Size Designation: 24 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
24 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):28Thread Size:1.500 inchesMaterial:Aluminum alloySurface Treatment:
1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Thready Qty Per Inch (tpi): 28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
28 Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
Thread Size: 1.500 inches Material: Aluminum alloy Surface Treatment:
1.500 inches Material: Aluminum alloy Surface Treatment:
Material: Aluminum alloy Surface Treatment:
Aluminum alloy Surface Treatment:
Surface Treatment:
Cadmium and chromate
Style Designator:
Straight type w/cable clamp
Surface Treatment:
Cadmium and chromate
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A10100