## NSN 5935-01-081-3153

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-081-3153

Body Style:
Angle shape, external coupling
Bushing Diameter:
0.162 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.340 inches
Overall Height:
0.617 inches
Overall Width:
0.500 inches
Environmental Protection:
Vibration resistant and salt water resistant and humidity resistant
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.340 inches
Distance From Mounting Shoulder To Rear Face:
0.180 inches
Flange Length:
0.500 inches
Mating End Quantity:
1
Shell Type:
Solid
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type i, class 2, grade c military specification single treatment response single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single
material response single mating end single contact grouping
Shell Material:
Stainless steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35, type i, ii, or iii federal specification single treatment response

Included Contact Quantity:

**Shell Material Specification:** 

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Qq-s-764, class 303, cond a federal specification single material response

## NSN 5935-01-081-3153

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surface gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.