

View Online at <https://aerobasegroup.com/nsn/5935-01-081-3736>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.290 inches

Overall Height:

1.812 inches

Overall Width:

1.812 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.157 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Distance From Mounting Shoulder To Front Face:

Between 0.785 inches and 0.790 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

24-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

345.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

18

Thread Size:

1.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, class 3 or 4, grade b military specification single treatment response

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Contact designation 25-35

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.128 gold grains, troy and 0.128 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27656 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/a

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.