Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-081-4713

Thread	Classe
Thread	Class:

2a

**Thread Direction:** 

Right-hand

### Body Style:

Straight shape

## **Overall Length:**

1.350 inches

#### **Overall Height:**

0.712 inches

#### **Overall Width:**

0.250 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

### Distance Between Mounting Facility Centers:

1.150 inches

# Threaded Device Type:

Mounting stud

#### Mating End Quantity:

1

#### Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### **Connector Locking Method:**

Friction

# Thready Qty Per Inch (tpi):

56

# Thread Size:

0.086 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic single mating end and glass fiber single mating end

Electrical Receptacle Connector - Page 2 of 2



# **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14g, ty gdi-30f or ty sdg-f military specification all material responses single mating end **Unable To Decode:** Unable to decode and unable to decode **Included Contact Quantity:** 20 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.