NSN 5935-01-081-6540

Connector Adapter - Page 1 of 2

Thread Class: 2a and 2b



View Online at https://aerobasegroup.com/nsn/5935-01-081-6540

Thread Direction: Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 2.060 inches **Overall Diameter:** 0.820 inches **Environmental Protection:** Humidity resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Tnc 2nd mating end **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Frequency Rating:** 11000.0 megahertz all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell and internally threaded coupling ring Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 28 and 24 **Thread Size:** 0.438 inches and 0.625 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic polytetrafluoroethylene all mating ends **Contact Surface Treatment Specification:** Mil-g-45204, type 1, grade c, cl 1 military specification single treatment response all mating ends single contact grouping **Contact Material Specification:** Qq-b-626, half hard federal specification single material response all mating ends single contact grouping

NSN 5935-01-081-6540

Connector Adapter - Page 2 of 2



Shell Material:
Steel
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shell Material Specification:
Qq-s-764, type 303 condition federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response all mating ends
Included Contact Quantity:
1 all mating ends single contact grouping
Included Contact Type:
Coaxial pin all mating ends single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.